



Rainfresh UCCSM system is a premium under-sink drinking water system that reduces harmful suspended and dissolved contaminants from water. It can be used on both treated and untreated waters (such as from lakes, rivers etc).

It incorporates a 2-stage filtration design that includes a high grade activated carbon filter followed by a ceramic filter. UCCSM

- Reduces >99.99% of sediment and particulate matter of 0.3 micron size
- Reduces > 99.99999 bacteria (e.g. E. coli) & > 99.95% cyst (Cryptosporidium & Giardia) & other parasites
- Reduces Volatile Organic Compounds (VOC), such as herbicides, pesticides
- Reduces chlorine, taste and odour

TESTING AND CERTIFICATION


UCCSM has been tested and certified by CSA International to CSA B483.1, to NSF/ANSI 53 for reduction of VOC and cysts, and to NSF/ANSI 42 for reduction of chlorine, taste and odour.

VOC reduction means that the system reduces the concentration of all the contaminants listed below by > 95%.

alachlor	1,2-dichloroethane	1,1,2,2,-tetrachloroethane	tetrachloroethylene
atrazine	1,1-dichloroethylene	heptachlor (H-34, Heptox)	toluene
benzene	cis-1,2-dichloroethylene	heptachlor epoxide	2,4,5-TP (silvex)
carbofuran	trans-1,2-dichloroethylene	hexachlorobutadiene	tribromoacetic acid
carbon tetrachloride	1,2-dichloropropane	hexachlorocyclopentadiene	1,2,4-trichlorobenzene
chlorobenzene	cis-1,3-dichloropropylene	lindane	1,1,1-trichloroethane
chloropicrin	dinoseb	methoxychlor	1,1,2-trichloroethane
2,4-D	endrin	pentachlorophenol	trichloroethylene
dibromochloropropane (DBCP)	ethylbenzene	simazine	xylene (total)
o-dichlorobenzene	ethylene dibromide (EDB)	styrene	trihalomethanes (includes)
p-dichlorobenzene	haloacetonitriles (HAN) bromochloroacetonitrile dibromoacetonitrile dichloroacetonitrile trichloroacetonitrile	haloketones (HK) 1,1-dichloro-2-propanone 1,1,1-trichloro-2-propanone	chloroform (surrogate chemical) bromoform bromodichloromethane chlorodibromomethane

It is also independently tested for reduction of coliform, E. coli & other bacteria (see below)

Contaminant	Reduction Efficiency	Log Reduction
BACTERIA		
E.coli (Faecal Coliform)	> 99.9999%	> 6 log
Serratia marcescens	> 99.9999%	> 6 log
Salmonella typhimurium (Typhoid)	> 99.9999%	> 6 log
Vibrio Cholera (Cholera)	> 99.9999%	> 6 log
Shigella dysenteriae (Dysentery)	> 99.9999%	> 6 log
Klebsiella terrigena	> 99.9999%	> 6 log



E. coli

FEATURES



Easy Open Housings - Just grab by hand, turn and remove. *No tools required!*

UCCSM Drinking Water System



Ceramic disc chrome faucet

UCCSM includes an all-chrome ceramic disc faucet and all fittings and tubing necessary to install the unit.



Cleanable and Reusable Ceramic Cartridge

The ceramic filter cartridge is cleanable & reusable. When fine dirt and particulates plug up the ceramic filter and reduce the water flow, the cartridge can be easily cleaned under tap water using a scrubber (included). A cartridge gauge is also included to verify when the cartridge eventually needs to be replaced.



Electronic Monitor – Indicates cartridge replacement time

UCCSM filter system features a fully metered “Cartridge Life Monitor” that sets off a visual indicator at the end of filter life or 6 months (whichever is earlier) at which point the cartridge need replacement. This unique feature helps maintain the efficiency of the filter system and reduces downtime.

SYSTEM DIMENSIONS

Model	Unit Width (Inch)	Unit Height (Inch)	Unit Depth (Inch)	Monitor Type
UCCSM	11.2"	13"	5"	Time & Gallon

TECHNICAL SPECIFICATIONS

Rated service flow	- 0.75 US GPM (2.83 LPM)
Inlet/Outlet	- 3/8" Tube
Operating Temp	- 4°C (39°F) min. to 38°C (100°F) max.
Working Pressure	- 40 psi (min) to 100 psi (689 KPa) max.

* A pressure regulator and/or water hammer arrestor must be installed before the unit to protect the unit from damage caused due to high pressure.



INSTALLATION

The UCCSM system is designed for undersink or any other wall mounted remote location from where tubing can be run to the faucet. The unit should not be installed more than fifteen feet away from the faucet. The unit includes all fittings and parts required to make connection to a copper pipe.

REPLACEMENT CARTRIDGES

Filter Cartridge Model	Cartridge Type	Rated Cartridge Life^
VC1	High grade activated carbon block	6 months or 600 US gal (2271 Litres)
1M	Ceramic filter	12 months or 1000 US gal (3785 Litres)

^ Cartridge life may vary with water quality and usage.



5 year limited warranty



Envirogard Products Limited

446, Major Mackenzie Drive East, Richmond Hill,
ON L4C 1J2, CANADA
Tel: (905) 884 9388 Fax: (905) 884 3532
Web: www.rainfresh.ca